800-634-8981

info@ameri-shred.com

AMS-1500HD & 2000HD HARD DRIVE SHREDDERS Durable, Powerful & Reliable

Options:

- Choice of shred width
- Powder coat color
- Hard drive counter
- Backlit laser burned logos
- Mobile truck installation
- Air particulate system: (See 2nd page)
- Infeed conveyor: (See 3rd page)

Benefits

- Minimal energy consumption
- Slow speed & high torque

SPECIFICATION CHART			
Motor	15 or 20 HP TEFC		
Shred Width	1-1/2", 1" or 3/4"		
Infeed	20" W x 4" H		
Voltage	208/230/460v 3 Phase		
Output	Discharge Conveyor		
Dimensions	94" L x 75" W x 67" H		



THROUGHPUT						
Model Number	Shred Width	Horse Power	Standard Drives / Hr.	Server Drives / Hr.	Speed (FPM)	Weight (Lbs.)
AMS-1500HD	1-1/2"	15 HP	2100	1050	40	4500
AMS-2000HD	1-1/2"	20 HP	2400	1200	44	4500
AMS-2000HD	1"	20 HP	1800	900	44	4500
AMS-2000HD	3/4"	20 HP	1200	600	44	4500

3/4" and 1" shred widths are only available on AMS-2000HD

800-634-8981

info@ameri-shred.com

AIR FILTRATION SYSTEMS Optional on Hard Drive Shredders Series 2 & Series 3

The AMS air filtration system was designed to help reduce possible odors and/or contaminants from escaping into the atmosphere during hard drive destruction.

Standard Features:

- Inexpensive and disposable pre-filter protects the blower and HEPA filter
- The blower is housed in cast aluminum
- The blast gate serves as an air flow control valve

SPECIFICATION CHART			
Motor	1 HP TEFC		
Air Flow	400 CFM at 3" static		
Efficiency	99.97% on particles 0.3		



Ameri-Shred's air filtration systems consist of six major components which include the inlet, pre-filter, blower, blast gate, HEPA filter and ductwork.

An air filtration system must be part of your original order. It cannot be retrofit at a later date.

800-634-8981 info@ameri-shred.com



Hopper Fed Infeed Conveyor

1 HP Motor, Variable Speed Controls **Cleated Belt, Heavy Duty Casters**