



800-634-8981 [info@ameri-shred.com](mailto:info@ameri-shred.com)

- ◇ Capable of Shredding up to 600 Solid State Drives Per Hour ◇
- ◇ Capable of Shredding up to 600 Rotary Drives Per Hour ◇

**SOLID STATE DRIVE SHREDDERS:**

AMS-150-SSD | AMS-300-SSD

**SSD & ROTARY DRIVE SHREDDERS:**

AMS-150HD-SSD | AMS-300HD-SSD

**Requirements:**

- Single phase power is only available on the AMS-150 models. It requires a dedicated 20 amp circuit & reduces throughput by 10%.
- AMS-300 models require three phase power.



SPECIFICATION CHART	
Motor	1.5 or 3 HP TEFC
Infeed	5" W x 2" H
SSD Shred Width	3/8"
Rotary Drive Shred Widths	1.5" or 3/4"
Voltage	120/208/230/460v 1 or 3 Phase
Output	Discharge Bin or Conveyor
Dimensions	53" W x 21" D x 44" H

THROUGHPUT						
Model Number	HP	Shred Widths	Solid State Drives / Hour	Standard Rotary Drives / Hour	Server Rotary Drives / Hour	Weight (Lbs.)
AMS-150-SSD	1.5	3/8"	180 - 200	N/A	N/A	1100
AMS-300-SSD	3	3/8"	550 - 600	N/A	N/A	1100
AMS-150HD-SSD	1.5	3/8" / 1.5"	180 - 200	180 - 200	90 - 100	1400
AMS-150HD-SSD	1.5	3/8" / 3/4"	180 - 200	90 - 100	45 - 50	1400
AMS-300HD-SSD	3	3/8" / 1.5"	550 - 600	550 - 600	275 - 300	1400
AMS-300HD-SSD	3	3/8" / 3/4"	550 - 600	275 - 300	135 - 150	1400