



## 2420-MTB-II Sealer

Also available as a 2420-GSM-II without conveyor

### FEATURES

- 24" x 20" seal area
- Self-adjusting seal pads
- Easy quick change Mono seal wire
- Fully welded heavy duty seal head
- Fully welded 11 gauge steel frame
- Heavy duty automatic dual magnets
- Adjustable height seal area platform
- Auto seal temperature compensator
- Variable speed soft start conveyor
- Stainless steel film hold downs
- Stainless steel product loading tray
- Quick lock wire tensioners
- Film tension brake
- Easy access slide out control panel
- Micro perforator
- Storage shelf and casters
- Hot knife option
- **TWO YEAR WARRANTY** (including seal wire)

Model	Max Product Size	Packages Per Minute	Area	Power Required	Machine Size L x W x H	Shipping (Size/Weight) L x W x H
2420-MTB-II	23" x 19" L x W	15 - 18	24" x 20" L x W	220 Volts 1 PH 15 Amps	63" x 42" x 40"	76" x 54" x 57" 645 lbs.

**Engineered to Perform. Designed to Endure.**



**Charles Beseler Company**

Packaging Division  
2018 West Main Street  
P.O. Box 431  
Stroudsburg, PA 18360

Toll Free: 800.237.3537  
P: 570.517.0400  
F: 800.966.4515  
Email: [customerservice@beseler.com](mailto:customerservice@beseler.com)

[www.beseler.com](http://www.beseler.com)