

# PC-P430

Paper Cutter

**Table-top Paper Cutter** for office efficiency and cost savings.



- 1. Maximum cut width is 434 mm / 17", maximum thickness is up to 23 mm / 0.9".
- 2. Minimum cut length is 50 mm / 1.97" for small format applications such as business cards.
- 3. Sheets are trimmed by simply setting the sheets and pressing the dual push buttons. An automatic clamping press for easy operation.
- 4. Illuminated cut line conveniently identifies the cut position for easy, accurate cutting.
- 5. Innovative cutting knife design for easy and safe knife replacement.

The perfect office cutter for cutting for cutting of printed sheets or trimming books.



**Push-out Lever** 

5 Cut Stick Lift Lever

The operator

simply pushes a

lever to move cut

sheets forward for

easy removal.

The cut stick is

easily replaced

integrated lift lever.

by using the

# **Dual Push Buttons**

The PC-P430 is activated only when the safety cover is closed and both cutting buttons are



simultaneously pressed. The two buttons are sufficiently spaced to ensure operator safety.

## Safety Full Cover

The front cover will not open during the operation. The full cover keeps your fingers away from the moving part.

# Safety Power Key

The power switch can be key activated to limit user access.

	PC-P430	Option
Pedestal with Wheels: MT-P43		
Maintenance Kit		
Item	Quantity	
Spare Knife with Sheath	2 pcs	
Cut Stick	10 ncs	

<sup>\*</sup>The machine design and specifications are subject to change without any notice.

# Horizon

# HORIZON INTERNATIONAL, INC.

510 Kuze Ooyabu-cho, Minami-ku, Kyoto, 601-8206, Japan Phone: +81-(0)75-934-6700 Fax: +81-(0)75-934-6708 www.horizon.co.jp

# 6 Cutting Line


Illuminated cut line conveniently identifies the cut position for easy sheet positioning.

## **Backgauge Handle**

Backgauge position can be adjusted by turning the handle.

# **Backgauge Free Mechanism**

Sheets longer than 320 mm / 12.5" can be trimmed using the backgauge free mechanism.



# 9 Cutting Knife Counter

Cut cycles are indicated on a digital counter to help determine when the cutting knife should be replaced.

# 10 Press Section

The sheets are pressed and cut automatically by pressing the cutting buttons. A special cutout is provided to prevent book spines from crushing.

# **Double Lead Screw System**

Accurate backgauge raceway keeps the gauge square to ensure accurate cutting.



PC-P430 Specifications			
Cutting Width	ĺm.	Max. 434 mm / 17.08"	
Cutting Height		Max. 23 mm / 0.9"	
Cutting Depth		Max. 320 mm / 12.59" Min. 50mm / 1.97"	
Clamp System	Spring-Operated		
Push-out Length	Max. 25 mm / 0.98"		
Cutting Speed	About 4 seconds per cycle (100 V, 60 Hz) About 4.8 seconds per cycle (100 V, 50 Hz)		
Voltage/Frequency	Single Phase 110 to 120 V, 60 Hz Single Phase 220 to 240 V, 50 / 60 Hz		
Rated Current	Single Phase 110 to 120 V, 60 Hz, 3.9 A Single Phase 220 to 240 V, 50 Hz, 1.6 A		
Machine Dimensions	W675 x D600 x H375 mm / W26.6" x D23.7" x H14.8"		
Machine Weight	66 kg / 145.4 lb		

Distributed by



Standard Finishing Systems, 10 Connector Road, Andover, MA 01810 877-404-4460 978-470-1920 Fax 978-470-2771 www.standardfinishing.com