

H20 - Dual Hot Roll



FEATURES

Variable speed. The laminator operates at any speed up to 10 feet / 3 meters per minute. Thicker hot films are generally applied better at mid-range to lower speeds, while 1.5 mil hot films should be applied at mid-range to higher speeds.

Attached safety shield. The polycarbonate shield is clear so operators can see their work. It does not conduct heat so they'll be protected from hot areas. It is fixed to the laminator and the machine will not run if the feed tray and safety shield are not in place.

Lamination pressure. The rubber rollers are spring-loaded and preset to ensure correct and even lamination pressure. The pressure is easy to adjust if required when performing routine maintenance.

Ease of cleaning. The heated silicone rubber laminating rollers, and the silicone rubber pull rollers of the laminator should be cleaned regularly. The safety shield (see below) on the laminator swings away in seconds, making it easy to clean the laminating rollers.

Precision Heat Controls. Individual top and bottom heat controls, as used

on our other Digital Laminators, allow for even, consistent heating of the laminating rollers throughout the entire temperature range.

Supply roll tension controls.

Supply roll tension is easy to adjust by simply tightening or loosening the tension control knobs on the supply roll mandrels.

Feed tray pressure strip. This strip on the front of the feed tray holds images flat as they go into the laminator, making it easier to handle the lightweight papers sometimes used in digital imaging.

Ease of maintenance. The H20 laminator is made to last. However, some items on a laminator do wear out. Even the high-quality silicone rubber used in the rollers will lose flexibility over time. Extensive use may wear out the rollers, or an operator may cut a roller by accident. Rollers and other key parts can be changed quickly without disassembling the frame.

LEDCCO INC.

H20

H20

H20

H20

H20 - Dual Hot Roll

Includes
Precision Feed Table
Stand & Casters
Slitter Assembly



Type of Heating	Hot Roll
Maximum Lamination Width	20"
Speed	0-10 FPM
Laminating Roller Diameter	2.75"
Supply Roll Core Size	3"
Recommended Film Thickness	Up to 10mil
Maximum Laminating Thickness	1/2"
Dimensions With Stand	52"Lx39"Hx32.5"D
Shipping Dimensions	56"Lx49"Hx43"D
Weight/Shipping Weight	250 / 450 lbs
Motor	1/4 HP DC - variable speed
Electrical	208-240V
	50/60 Hz
	Single Phase 10 amps
Electric Supply Plug	NEMA L6-20P
Heater	1500 watts



a Graphic Laminating company
4265 North Main Street • Hemlock, NY 14466
Phone: 800-345-5300

